



21 July 2010

ASX Announcement

Further high grade nickel, cobalt & scandium in follow-up drilling on Lucknow deposit within NORNICO project (Qld)

- Additional high grade scandium (Sc) zones intersected between Grants Gully and Red Fort scandium deposits
- Broad shallow high grade Sc zones also confirmed
- Additional high-grade Ni-Co mineralisation identified at Lady Agnes and Grants Gully areas
- Results are from Phase 2 follow-up drilling of 142 new holes drilled for 3,516m – Figure 1
- Resource study commenced, maiden Lucknow Ni-Co & Sc resource estimate expected soon
- Drilling results from nearby Greenvale also due shortly.


Lucknow Ni-Co & Sc Project

New follow-up drilling completed this month has confirmed continuous scandium mineralised zones including high grade intersections, in two target areas of Metallica Minerals Limited's Lucknow nickel-cobalt and scandium project near Greenvale within the southern area of the Company's flagship NORNICO project northwest of Townsville in Queensland.

The drilling also increased the size of the known nickel-cobalt mineralisation in the area including additional high grade Ni-Co intercepts.

As a result, the assay data from the two drill programs at Lucknow is now being collated to provide a maiden nickel-cobalt resource and a separate scandium resource for

Figure 1: Lucknow Phase 1 and Phase 2 Drill Hole Locations



**LUCKNOW Ni - Co - Sc PROJECT
DRILLING PROGRAM 2010**



Lucknow. These resource estimates are expected by early August and Metallica will include the estimates in its Stage 1 scoping study for the broader NORNICO project which is assessing sourcing high grade Ni-Co and Sc zones for initial mill feed for a 180,000 tonnes per annum processing plant.

Commenting on the results, Metallica's Managing Director, Mr Andrew Gillies, said:

"Further confirmation of more high grade Ni-Co and Ni-Co-Sc zones as well as broad and thick Sc zones, suggests these results will lead to very high metal values in the Lucknow ore, given that Metallica's intention is to recover all three metals at the same time."

"Significantly, the drilling at Lucknow has defined a second large and discrete, high grade scandium orebody similar to our Kokomo scandium resource so there is increasing confidence that Lucknow, and the pending results from the Greenvale drilling area just to the west of Lucknow, will be major contributors to achieving our initial high grade production target from NORNICO Stage 1 processing."

"We expect the pending resource estimates for the respective Lucknow Ni-Co-Sc and Greenvale Ni-Co deposits and their incorporation into the current NORNICO stage 1 scoping study, will add to that belief."

Lucknow deposit profile

The Lucknow Ni-Co & Sc laterite deposit is located approximately 2km southwest of the Greenvale township and approximately 6km southeast of the Greenvale nickel mine in north Queensland. The Lucknow Ni-Co-Sc deposit is covered by 2 EPM's (EPM 10680 and EPM 10866) held by Greenvale Operations Pty Ltd, a wholly-owned subsidiary of Metallica. Metallica holds 100% of the Ni-Co and other mineral rights and 80% of the Sc ore rights, with scandium joint venture partner, Straits Resources Ltd, holding the remaining 20% of the scandium ore rights.

In April 2010, Metallica completed an initial drilling campaign at Lucknow (Phase 1) to define and better delineate high grade zones of Ni-Co mineralisation intersected by previous explorers. The Phase 1 drilling at Lucknow comprised a total of 156 holes (LKRC-013 to LKRC-168) for a total of 3,520m. (*Results from this program are summarised in ASX Release dated 10th May 2010.*)

In addition to intersecting and defining significant Ni-Co mineralisation at two areas on Lucknow (Grants Gully and Lady Agnes), the Phase 1 drilling program discovered high grade scandium mineralisation on the NNE Lucknow trending ridge-plateau. One hole, LKRC-99, recorded 27m at 882 g/t Sc from surface. Scandium is generally associated with Ni-Co mineralisation at Grants Gully, with broad zones of strong scandium mineralisation also found at an area of low Ni-Co mineralisation, referred to as Red Fort.



The Phase 2 drilling program completed this month at Lucknow was designed to follow up the high grade nickel-cobalt and scandium mineralisation identified at Grants Gully, Lady Agnes and Red Fort. The Phase 2 program comprised 142 holes (LKRC-169 to LKRC-310) for a total of 3,516m. The drilling was also designed to infill an area between Grants Gully and Red Fort to determine if the scandium mineralisation is continuous between these two areas. Drilling was completed on a 20m by 20m grid or on a wider 80m (N-S) by 40m (E-W) grid pattern. **Figure 1** shows the additional drill hole locations for the phase 2 drilling.

Phase 2, Nickel (Ni) – Cobalt (Co) drilling results

Drilling around the Lady Agnes and Grants Gully Ni-Co areas increased the size of the known mineralisation at both of these areas with an 80m by 80m zone of high grade nickel-cobalt mineralisation identified at Lady Agnes and additional high grade nickel-cobalt mineralisation identified to the south and south west of the Phase 1 drilling at Grants Gully.

Better intercepts from the Phase 2 drilling include:-


Lady Agnes

- LKRC-171, 4m @ 1.03% Ni, 0.41% Co, (1.85% Ni Eq¹)
- LKRC-173, 9m @ 0.73% Ni, 0.30% Co (1.33% Ni Eq)
- LKRC-178, 10m @ 1.04% Ni, 0.32% Co (1.68% NiEq)

Grants Gully

- LKRC-192, 6m @ 1.25% Ni, 0.24% Co and 69 g/t Sc (1.73% NiEq)
- LKRC-200, 9m @ 0.86% Ni, 0.75% Co and 344 g/t Sc (2.36% NiEq)
- LKRC-209, 5m @ 0.85% Ni, 0.71% Co and 66 g/t Sc (2.27% NiEq)
- LKRC-221, 8m @ 1.14% Ni, 0.53% Co and 99 g/t Sc (2.20% NiEq)
- LKRC-227, 6m @ 0.69% Ni, 0.49% Co and 138 g/t Sc (1.67% NiEq)

¹ Ni Eq (Nickel equivalency) is defined by Ni+2Co using prices for nickel of \$9/lb and \$18/lb for Cobalt assuming similar recoveries, no scandium mineralisation is included in the Ni equivalency calculation

Figure 2: Grants Gully Cross Section 7,894,900mN

Scandium (Sc) drilling Results (Phase 2)

Drilling has confirmed there is a wide and thick zone of continuous scandium mineralisation between Red Fort and Grants Gully. High grade scandium mineralisation was intersected in a number of holes at Grants Gully, typically with the associated high grade nickel-cobalt mineralisation occurring at the base of the scandium mineralisation in the laterite profile. High grade scandium mineralisation was also identified in several holes drilled around the Red Fort area, which has increased the size of this area from a 120m by 120m area to an area in excess of 400m by 200m with an average length of drill intercept of between 15-20m of high grade scandium mineralisation. The scandium mineralisation is open to the south of the Red Fort Zone.

Better Sc holes of the Phase 2 drilling include:-

Grants Gully:

- LKRC-296, 21m @ 242 g/t Sc from 0m
- LKRC-200, 12m @ 304 g/t Sc from 0m
- LKRC-202, 16m @ 345 g/t Sc from 14m
- LKRC-205, 21m @ 430 g/t Sc from 0m
- LKRC-206, 28m @ 340 g/t Sc from 0m

A cross section through the southern part of Grants Gully is presented in **Figure 2** and a metal distribution map for Grants Gully is included as **Figure 4**.

Between Grants Gully and Red Fort


- LKRC-216, 17m @ 324g/t Sc from 0m
- LKRC-217, 23m @ 401g/t Sc from 0m
- LKRC-223, 14m @ 279g/t Sc from 0m
- LKRC-232, 14m @ 229g/t Sc from 4m
- LKRC-247, 16m @ 226g/t Sc from 2m

Red Fort

- LKRC-254, 8m @ 432g/t Sc from 7m
- LKRC-260, 10m@ 223g/t Sc from 4m
- LKRC-271, 17m @ 257g/t Sc from 8m
- LKRC-280, 14m @ 249g/t Sc from 3m
- LKRC-289, 16m @ 231g/t Sc from 1m

A cross section through Red Fort is presented on **Figure 3** below, and the results from the Phase 2 drilling are included in **Table 1** appended to this report:

Figure 3: Red Fort Cross Section, 7,894,080mN





Maiden Lucknow resource estimates being prepared

The assay, geological and survey data from both the Phase 1 and 2 drilling programs at Lucknow has been uploaded into an Access database now forwarded to Golder Associates of Brisbane. Golder Associates completed a site visit to both the Lucknow and Greenvale deposits in March 2010 and have now commenced resource studies on the Lucknow deposit. A maiden resource estimate for the nickel-cobalt mineralisation as well as a separate scandium resource is currently being estimated for Lucknow and is expected to be available late in July - early August.

Potential feedstock for first processing

The resource base for Lucknow and Greenvale deposits will be incorporated into the current NORNICO Stage 1 scoping study. To maximise metal revenues combined high grade Ni-Co and Sc zones will be the focus for resource-reserve evaluation for providing selected Ni-Co and Sc ore feed volumes for the proposed NORNICO Stage 1 Ni-Co and Sc ore processing plant (size ~180,000 tpa). The scoping study is currently being finalised and a summary of the study outcomes is expected in the next couple of weeks.

Drilling results for Greenvale are also being finalised and are expected to be released shortly.

Photograph 1: RC Drilling at Grants Gully - Lucknow






Figure 4: Grants Gully Metal factor Map



LUCKNOW: Grants Gully Ni - Co & Sc Zone - Metal Distribution Plan





About Scandium

Scandium (Sc - element 21- next to zirconium, yttrium and titanium) is a Rare Earth Metal which has the potential to significantly enhance and possibly revolutionise the "Green Economy". It is currently used in fuel cells, high strength low weight aluminium alloys (AlSc), high intensity lamps and structural ceramics (PSZ). The lack of readily available and reliable long term scandium supply in the market has limited its commercial applications to date.

Scandium is generally marketed as scandium oxide (e.g. 99.9% purity) which sells for more than US\$1,400 per kilogram (kg).

Scandium bearing aluminium alloys (ScAl) is increasingly being used in a number of industries including aerospace, automotive, sporting equipment and mobile consumer electronics. Scandium stabilised zirconia (ScSZ) is a critical component of high efficiency Solid Oxide Fuel Cells (SOFC's). Partially stabilized ScSZ has the potential to replace high strength alloys in mechanical and aerospace applications.

Scandium has similar properties to other important and commonly used elements, such as titanium, zircon and rare earth yttrium. All three are currently used in a broad range of commercial applications and Scandium has similar characteristics that – in combination make it an extremely desirable element, however, with limited reliable supplies available it has been difficult to establish a strong market base beyond its current uses – hence an opportunity for Metallica.

For further information on scandium – *for more detailed information on Scandium - see ASX Release dated 10 May 2010.*


For further information

Andrew Gillies
Managing Director
Metallica Minerals Limited
(07) 3249 3000

Kevin Skinner
Partner
Field Public Relations
(08) 8234 9555 or 0414 822 631

Competent Persons

Technical information and exploration results contained in this report has been compiled by Metallica Minerals Ltd full time employees Andrew Gillies in the position of Managing Director and Metallica Minerals Ltd Exploration Manager, Mr Pat Smith MSc. B.Sc (Hons). Mr Gillies and Mr Smith are members of the Australasian Institute of Mining and Metallurgy and have relevant experience to the mineralisation being reported on to qualify as Competent Persons as defined by the Australasian Code for Reporting of Minerals Resources and Reserves. Mr Gillies and Mr Smith consent to the inclusion in this report of the matters based on the information in the form and context in which it appears



Lucknow - Ni - Co - Sc Deposit: Phase 2 Drilling (LKRC-169 to LKRC-310)

Hole Number	Easting	Northing	Depth	From	To	Intercept	Ni (%)	Co (%)	Sc (g/t)	NiEq ¹	Fe (%)	Mg (%)
LKRC-169	285355	7895575	27	13	22	9	0.50	0.22	12	0.94	18.37	1.01
LKRC-170	285355	7895595	30	8	21	13	0.47	0.19	12	0.85	16.06	1.10
LKRC-171	285355	7895615	27	6	17	11	0.68	0.29	27	1.26	25.76	0.61
inc.				6	10	4	1.03	0.41	61	1.85	34.15	1.20
LKRC-172	285355	7895635	21	11	14	3	1.04	0.22	33	1.48	28.60	2.40
LKRC-173	285355	7895655	27	11	20	9	0.73	0.30	22	1.33	29.38	1.06
inc.				12	16	4	0.93	0.41	31	1.75	38.25	1.90
LKRC-174	285355	7895675	27	14	19	5	1.28	0.27	27	1.82	32.42	1.77
LKRC-175	285335	7895655	33	11	19	8	0.55	0.19	12	0.93	18.60	0.31
and				22	24	2	1.32	0.05	26	1.42	15.15	1.10
LKRC-176	285355	7895675	27	13	21	8	0.65	0.28	12	1.21	20.71	0.38
LKRC-177	285335	7895655	33	13	24	11	0.62	0.24	12	1.10	17.77	1.05
inc				15	19	4	0.63	0.40	12	1.43	21.00	0.35
LKRC-178	285335	7895595	24	8	18	10	1.04	0.32	24	1.68	33.89	1.27
inc.				11	17	6	1.31	0.45	30	2.21	36.75	1.83
LKRC-179	285335	7895575	24	10	19	9	0.35	0.12	10	0.59	19.94	0.24
LKRC-180	285400	7895575	27	15	22	7	0.40	0.20	7	0.80	14.78	0.27
LKRC-181	285400	7895595	27	6	22	16	0.52	0.20	15	0.92	27.05	0.42
				8	12	4	0.61	0.25	19	1.11	33.82	0.41
LKRC-182	285400	7895615	24	8	19	11	0.64	0.21	17	1.06	0.52	0.52
				10	14	4	0.73	0.31	20	1.35	0.42	0.42
LKRC-183	285400	7895635	21	NSR								
LKRC-184	285400	7895655	24	NSR								
LKRC-185	285420	7895580	24	15	20	5	0.29	0.13	3	0.55	10.78	0.28
LKRC-186	285420	7895600	24	3	18	15	0.39	0.14	13	0.67	20.67	0.27
LKRC-187	285420	7895620	33	5	25	20	0.60	0.21	20	1.02	26.42	0.59
inc:				20	23	3	0.99	0.39	17	1.77	35.10	0.84
LKRC-188	285420	7895640	39	9	19	10	0.72	0.23	22	1.18	37.72	0.52

¹ NiEq – is calculated using Ni+2Co – based on Ni price of \$9/lb and a Cobalt price of \$18/lb

Hole Number	Easting	Northing	Depth	From	To	Intercept	Ni (%)	Co (%)	Sc (g/t)	NiEq	Fe (%)	Mg (%)
LKRC-189	285420	7895660	36	NSR								
LKRC-190	284760	7894960	12	0	5	5	0.16	0.03	137	0.22	24.26	1.70
LKRC-191	284740	7894960	12	2	7	5	0.55	0.05	104	0.65	19.28	3.87
LKRC-192	284800	7894940	30	13	19	6	0.41	0.09	139	0.59	42.28	0.40
and				19	25	6	1.25	0.24	69	1.73	27.03	4.45
LKRC-193	284780	7894940	12	1	8	7	0.13	0.02	191	0.17	29.28	0.40
and				8	10	2	0.58	0.46	146	1.50	9.27	5.68
LKRC-194	284760	7894940	12	0	6	6	0.12	0.01	178	0.14	28.63	1.34
LKRC-195	284740	7894940	18	6	18	12	0.18	0.04	228	0.26	26.68	2.79
LKRC-196	284800	7894920	21	0	21	21	0.26	0.05	242	0.36	33.62	1.49
inc:				8	17	9	0.38	0.08	366	0.54	37.58	1.05
LKRC-197	284780	7894920	21	0	15	15	0.12	0.01	194	0.14	35.45	0.22
and				15	18	3	0.63	0.34	167	1.31	18.83	3.41
LKRC-198	284760	7894920	21	0	20	20	0.08	0.02	196	0.12	27.96	0.94
LKRC-199	284740	7894920	18	5	15	10	0.07	0.01	208	0.09	31.09	0.19
LKRC-200	284800	7894900	21	0	12	12	0.10	0.02	304	0.14	37.36	0.18
and				12	21	9	0.86	0.75	344	2.36	19.90	2.40
LKRC-201	284780	7894900	21	0	11	11	0.11	0.01	111	0.13	37.91	0.12
LKRC-202	284760	7894900	30	14	30	16	0.04	0.01	345	0.06	29.83	0.73
inc:				17	27	10	0.04	0.01	441	0.06	32.71	0.66
LKRC-203	284740	7894900	21	3	17	14	0.10	0.01	180	0.12	41.38	0.13
				17	20	3	0.51	0.14	206	0.79	13.38	4.06
LKRC-204	284720	7894900	18	2	13	11	0.14	0.01	158	0.16	36.39	0.11
and				13	15	2	0.66	0.22	63	1.10	20.50	2.84
LKRC-205	284830	7894890	21	0	21	21	0.10	0.03	430	0.16	31.70	2.02
inc				6	17	11	0.07	0.01	651	0.09	35.91	0.61
LKRC-206	284840	7894900	30	0	28	28	0.13	0.02	340	0.17	25.18	2.17
inc.				6	14	8	0.07	0.01	586	0.09	31.25	0.10
LKRC-207	284860	7894900	36	2	13	11	0.32	0.02	204	0.36	42.54	0.18
and				17	24	7	0.76	0.31	91	1.38	45.01	0.44
LKRC-208	284880	7894897	18	4	7	3	0.15	0.01	142	0.17	35.70	0.12
and				7	10	3	0.86	0.51	184	1.88	17.36	4.59
LKRC-209	284900	7894900	24	8	22	14	0.62	0.38	57	1.38	41.41	0.32
and				12	17	5	0.85	0.71	66	2.27	52.36	0.35

Hole Number	Easting	Northing	Depth	From	To	Intercept	Ni (%)	Co (%)	Sc (g/t)	NiEq	Fe (%)	Mg (%)
LKRC-231	284640	7894620	24	NSR								
LKRC-232	284800	7894540	24	4	18	14	0.16	0.02	229	0.20	40.92	0.28
and				18	21	3	0.41	0.21	133	0.83	24.87	1.68
LKRC-233	284760	7894540	24	0	3	3	0.16	0.02	136	0.20	43.13	0.24
LKRC-234	284720	7894540	21	NSR								
LKRC-235	284680	7894540	27	22	27	5	0.22	0.02	174	0.26	11.76	6.87
LKRC-236	284640	7894540	24	10	14	4	0.19	0.01	113	0.21	32.95	0.45
and				15	19	4	0.47	0.14	40	0.75	44.85	1.01
LKRC-237	284800	7894460	21	5	20	15	0.29	0.06	205	0.41	34.83	1.70
LKRC-238	284760	7894460	21	NSR								
LKRC-239	284720	7894460	21	13	19	6	0.29	0.27	20	0.83	12.89	0.50
LKRC-240	284680	7894460	24	NSR								
LKRC-241	284640	7894460	21	6	18	12	0.23	0.05	191	0.33	23.42	2.89
LKRC-242	284800	7894380	24	2	20	18	0.14	0.03	174	0.20	27.89	1.08
LKRC-243	284760	7894380	24	2	19	17	0.32	0.06	193	0.44	35.88	1.38
LKRC-244	284720	7894380	27	3	24	21	0.28	0.11	210	0.50	28.88	2.39
inc				5	12	7	0.17	0.02	289	0.21	40.63	0.31
and				12	17	5	0.62	0.38	160	1.38	22.72	2.72
LKRC-245	284680	7894380	27	0	5	5	0.18	0.02	156	0.22	44.32	0.14
and				15	21	6	0.78	0.08	92	0.94	18.52	5.72
LKRC-246	284640	7894380	21	0	13	13	0.20	0.02	210	0.24	38.50	0.44
and				13	18	5	0.92	0.10	90	1.12	30.14	3.36
LKRC-247	284600	7894380	24	2	18	16	0.12	0.01	226	0.14	33.88	0.22
and				18	20	2	0.60	0.46	110	1.52	19.25	2.59
LKRC-248	284800	7894300	21	2	10	8	0.19	0.02	251	0.23	35.35	0.24
and				10	16	6	0.60	0.51	259	1.62	17.22	2.30
LKRC-249	284760	7894300	24	4	15	11	0.17	0.01	214	0.19	36.89	0.17
and				16	19	3	0.57	0.29	92	1.15	19.77	2.44
LKRC-250	284720	7894300	18	5	12	7	0.18	0.01	162	0.20	32.87	0.19
LKRC-251	284680	7894300	18	0	5	5	0.23	0.02	142	0.27	45.36	0.16
LKRC-252	284640	7894300	24	4	13	9	0.20	0.02	153	0.24	38.80	0.16
LKRC-253	284800	7894260	21	8	18	10	0.18	0.05	290	0.28	29.07	1.03
inc				11	16	5	0.14	0.01	432	0.16	29.12	1.15

Hole Number	Easting	Northing	Depth	From	To	Intercept	Ni (%)	Co (%)	Sc (g/t)	NiEq	Fe (%)	Mg (%)
LKRC-254	284760	7894260	27	4	19	15	0.15	0.03	338	0.21	35.17	0.72
inc				7	15	8	0.13	0.02	450	0.17	32.30	0.77
LKRC-255	284720	7894260	21	5	15	10	0.17	0.04	218	0.25	37.13	0.57
LKRC-256	284680	7894260	27	0	12	12	0.14	0.01	177	0.16	35.72	0.15
LKRC-257	284640	7894260	30	3	11	8	0.16	0.04	154	0.24	41.11	0.11
and				16	25	9	0.48	0.36	97	1.20	36.64	0.15
LKRC-258	284820	7894120	27	2	10	8	0.33	0.03	131	0.39	44.76	0.10
and				15	25	10	1.02	0.54	22	2.10	23.50	4.43
LKRC-259	284820	7894160	27	1	9	8	0.20	0.02	151	0.24	44.82	0.12
and				18	25	7	0.36	0.21	20	0.78	16.67	0.45
LKRC-260	284814	7894200	27	4	14	10	0.17	0.02	223	0.21	38.64	0.39
and				14	20	6	0.79	0.47	202	1.73	20.58	2.55
and				20	25	5	0.36	0.03	145	0.42	14.80	5.88
LKRC-261	284820	7894240	24	5	21	16	0.20	0.06	218	0.32	29.29	2.30
inc:				9	15	6	0.12	0.01	319	0.14	39.17	0.43
LKRC-262	284860	7894240	33	5	9	4	0.18	0.02	188	0.22	42.45	0.18
and				14	29	15	0.74	0.23	53	1.20	37.96	0.97
LKRC-263	284860	7894200	21	NSR								
LKRC-264	284860	7894160	27	16	24	8	0.26	0.19	8	0.64	13.35	0.28
LKRC-265	284860	7894120	39	20	31	11	0.30	0.19	5	0.68	10.01	3.97
LKRC-266	284800	7894080	27	NSR								
LKRC-267	284840	7894080	27	NSR								
LKRC-268	284880	7894080	27	NSR								
LKRC-269	284760	7894080	27	14	24	10	0.83	0.24	92	1.31	15.73	5.61
LKRC-270	284720	7894080	24	7	12	5	0.20	0.02	129	0.24	36.16	0.12
and				16	19	3	0.42	0.01	147	0.44	32.73	1.60
LKRC-271	284680	7894080	30	8	25	17	0.16	0.05	257	0.26	35.71	0.31
inc:				15	24	9	0.18	0.08	349	0.34	39.97	0.32
LKRC-272	284640	7894080	24	3	23	20	0.16	0.05	221	0.26	31.72	1.05
inc:				11	20	9	0.11	0.01	317	0.13	36.34	0.24
LKRC-273	284600	7894080	21	4	16	12	0.20	0.05	184	0.30	33.82	1.02
LKRC-274	284560	7894080	30	5	10	5	0.13	0.01	147	0.15	33.84	0.08
and				13	23	10	0.20	0.05	280	0.30	34.79	0.76

Hole Number	Easting	Northing	Depth	From	To	Intercept	Ni (%)	Co (%)	Sc (g/t)	NiEq	Fe (%)	Mg (%)
LKRC-275	284800	7894040	24	NSR								
LKRC-276	284760	7894040	30	23	26	3	0.35	0.29	49	0.93	17.70	0.64
LKRC-277	284720	7894040	27	11	17	6	0.27	0.02	234	0.31	41.97	0.33
and				17	20	3	1.11	0.32	85	1.75	14.80	5.23
LKRC-278	284680	7894040	30	9	20	11	0.21	0.02	182	0.25	44.32	0.28
and				20	23	3	0.69	0.47	117	1.63	21.13	2.83
LKRC-279	284640	7894040	33	6	18	12	0.23	0.02	176	0.27	48.82	0.11
and				23	28	5	0.62	0.22	205	1.06	27.70	2.83
LKRC-280	284600	7894040	21	3	17	14	0.16	0.01	249	0.18	38.28	0.85
and				17	19	2	0.53	0.33	170	1.19	15.15	5.23
LKRC-281	284560	7894040	30	7	19	12	0.36	0.03	199	0.42	48.93	0.18
and				22	26	4	0.77	0.32	60	1.41	39.55	1.40
LKRC-282	284520	7894040	24	6	20	14	0.09	0.02	308	0.13	35.47	0.22
and				20	22	2	0.46	0.24	186	0.94	22.85	2.14
LKRC-283	284520	7894080	21	5	15	10	0.07	0.01	162	0.09	26.72	0.27
and				15	17	2	1.03	0.86	266	2.75	11.60	2.99
LKRC-284	284800	7894000	24	NSR								
LKRC-285	284760	7894000	24	NSR								
LKRC-286	284722	7894000	24	NSR								
LKRC-287	284680	7894000	30	20	23	3	0.96	0.39	50	1.74	22.83	3.78
LKRC-288	284638	7894000	24	NSR								
LKRC-289	284598	7893998	24	1	17	16	0.12	0.01	231	0.14	35.62	0.26
and				17	20	3	0.36	0.54	262	1.44	17.52	2.99
LKRC-290	284570	7893999	24	6	20	14	0.15	0.03	232	0.21	31.11	1.19
LKRC-291	284535	7894000	30	9	21	12	0.32	0.03	149	0.38	52.98	0.25
and				21	25	4	0.64	0.38	146	1.40	31.62	1.19
LKRC-292	284840	7894700	30	NSR								
LKRC-293	284840	7894780	33	24	28	4	0.65	0.23	15	1.11	16.17	0.39
LKRC-294	284840	7894860	36	1	25	24	0.18	0.03	280	0.24	40.27	0.13
and				28	30	2	0.73	0.26	53	1.25	16.80	2.55
LKRC-295	284900	7894885	24	7	21	14	0.63	0.16	61	0.95	47.82	0.39
LKRC-296	284920	7894887	18	7	13	6	0.74	0.53	68	1.80	36.07	0.34
LKRC-297	284940	7894880	15	2	8	6	0.86	0.10	27	1.06	31.60	0.39

Hole Number	Easting	Northing	Depth	From	To	Intercept	Ni (%)	Co (%)	Sc (g/t)	NiEq	Fe (%)	Mg (%)
LKRC-298	284940	7894900	21	1	9	8	0.53	0.18	69	0.89	34.99	0.42
LKRC-299	284960	7894900	15	4	7	3	0.81	0.18	25	1.17	23.97	2.43
LKRC-300	285440	7895640	30	6	18	12	0.79	0.20	35	1.19	36.53	0.66
inc				9	15	6	0.85	0.25	32	1.35	43.22	0.38
LKRC-301	285320	7895580	24	7	15	8	0.54	0.18	20	0.90	22.00	0.56
inc				9	10	1	0.95	0.39	23	1.73	29.80	1.17
LKRC302	284784	7894982	21			Results	Pending					
LKRC303	284760	7894980	9			Results	Pending					
LKRC304	284720	7894960	24			Results	Pending					
LKRC305	284700	7894960	21			Results	Pending					
LKRC306	284720	7894940	21			Results	Pending					
LKRC307	284700	7894940	30			Results	Pending					
LKRC308	284724	7894920	30			Results	Pending					
LKRC309	284704	7894920	30			Results	Pending					
LKRC310	284687	7894915	24			Results	Pending					

NSR (No Significant Results - No Intercepts Greater than 1% Ni or 0.10%

Co or 100 g/t Sc over a 2m interval)